

型號	噴嘴 Nozzle	噴蓋 Air Cap	進氣壓力 Inlet Pressure	噴距 Distance	幅長 Pattern Length	幅寬 Pattern Width	噴幅圖數 Pattern adjustment	油漆固數 Fluid adjustment	油漆流量 Fluid Flow Rate	空氣流量 Air Consumption	空壓機 Air Compressor	開槍時間 Trigger Time	重量 Weight	
Model	(mm)	Type	kgf/cm (psi)	cm(in)	cm (in)	cm(in)	(Turn)	(Turn)	ml/min	l/min (cfm)	kW(HP)	sec	g(lb)	
A30 Plus (Spot Repair)	Basecoat Testing Data													260 (0.57)
	0.8	SR	1.0(14.5)	15(5.9)	16(6.3)	6(2.4)	全(Full)		83	90	Minimum(至少) 1.1kW (1.5HP) or Above 或以上	0.5		
	1.0				17(6.7)	6(2.4)			105					
	Clearcoat Testing Data													
	0.8	SR	1.0(14.5)	15(5.9)	12(4.7)	4.5(1.8)	全(Full)		83	90	Minimum(至少) 1.1kW (1.5HP) or Above 或以上	1		
	1.0				14(5.5)	5(2)			105					
Tested in Solvent Basecoat & Clearcoat	Data was tested under temperature 22 ℃ : humidity 49%													