

型號	噴嘴 Nozzle	噴蓋 Air Cap	進氣壓力 Inlet Pressure	噴距 Distance	幅長 Pattern Length	幅寬 Pattern Width	噴幅圈數 Pattern adjustment	油漆圈數 Fluid adjustment	油漆流量 Fluid Flow Rate	空氣流量 Air Consumption	空壓機 Air Compressor	開槍時間 Trigger Time	重量 Weight	
Model	(mm)	Type	kgf/cm (psi)	cm(in)	cm (in)	cm(in)	(Turn)	(Turn)	ml/min	l/min (cfm)	kW(HP)	sec	g(lb)	
A30 plus	Basecoat Testing Data												260(0.57)	
	0.8	A30 Ti1	2.0/29	15(5.9)	21(8.3)	5.5(2.2)	全(Full)	全(Full)	112	色漆 Base	180(6.4)	Minimum(至少) 1.5kW(2HP) or Above 或以上		0.5
	1.0	A30 CH	2.0/29	18(7.5)	27(10.6)	9(3.5)	全(Full)	全(Full)	150		235(8.3)			1
		A30 FX1	2.0/29	18(7.5)	26(10.2)	8(3.1)	2	全(Full)	170		185(6.5)			
	1.2	A30 CH	2.0/29	18(7.5)	28(11)	8(3.1)	全(Full)	全(Full)	205		215(7.6)			
	1.3	A30 CH	2.0/29	18(7.5)	29(11.4)	9(3.5)	3	全(Full)	220		215(7.6)			
	1.4	A30 CH	2.0/29	18(7.5)	31(12.2)	9.5(3.7)	3	全(Full)	220		215(7.6)			
	1.5	A30 CH	2.0/29	18(7.5)	31(12.2)	9.5(3.7)	2.5	全(Full)	230		215(7.6)			
	Clearcoat Testing Data													
	0.8	A30 Ti1	2.0/29	15(5.9)	18(7)	5(2)	全(Full)	全(Full)	112	清漆 Clear	180(6.4)	Minimum(至少) 1.5kW(2HP) or Above 或以上		1
	1.0	A30 CH	2.0/29	18(7.5)	20(7.9)	4.5(1.8)	全(Full)	全(Full)	150		235(8.3)			
		A30 FX1	2.0/30	18(7.5)	20(7.10)	4(1.6)	全(Full)	全(Full)	170		185(6.5)			
	1.2	A30 CH	2.0/29	18(7.5)	22(8.7)	4.5(1.8)	全(Full)	全(Full)	205		215(7.6)			
	1.3	A30 CH	2.0/29	18(7.5)	24(9.5)	5(2)	全(Full)	全(Full)	220		215(7.6)			
	1.4	A30 CH	2.0/29	18(7.5)	27(10.6)	7(2.8)	全(Full)	全(Full)	220		215(7.6)			
	1.5	A30 CH	2.0/29	18(7.5)	27(10.6)	7(2.8)	全(Full)	全(Full)	230		215(7.6)			
Tested in Solvent Basecoat & Clear coat													Data was tested under temperature 27 ℃ : humidity 42%	