

型號	噴蓋	噴嘴	針閥	進氣壓力	噴距	開槍時間	幅長	幅寬	噴幅圈數	油漆圈數	最大空氣流量	空壓機	油漆流量	重量
Model	Air cap	Nozzle	Needle	Inlet pressure	Distance	Trigger time	Pattern length	Pattern width	Pattern control knob	Fluid control knob	Max air consumption	Air compressor	Fluid flow rate	Weight
	Type	(mm)		kgf/cm (psi)	cm(in)	sec	cm (in)	cm (in)	圈(Turn)	圈(Turn)	l/min(cfm)	kW(HP)	ml/min	g(oz)
A60 eXtreme	UTE pro (HTE)	1.2	A60-121314	2.0(29)	20 (7.9)	1	37(14.6)	9(3.5)	2	全(Full)	360(12.7)	Minimum or Above 3.7kW(5HP) 或以上	200	360(12.7)
		1.3					37(14.6)	9(3.5)	2.0~2.5				260	
		1.4					37(14.6)	9(3.5)	2				290	
		1.5					A60-1.5	37(14.6)	8.5(3.3)				1.3~1.5	
	UHL (HVLP)	1.2	A60-121314	2.0(29)	20 (7.9)	1	34(13.3)	9(3.5)	3	全(Full)	460(16.2)	Minimum or Above 4.1kW (5.5HP) 或以上	200	
		1.3					34(13.3)	9(3.5)	3				230	
		1.4					36(14.2)	9(3.5)	3				260	
		1.5					A60-1.5	36(14.2)	9(3.5)				2.7	
	UMP (LVMP)	1.2	A60-121314	2.0(29)	20 (7.9)	1	31(12.2)	9(3.5)	全(Full)	全(Full)	290(10.2)	Minimum or Above 2.2kW(3HP) 或以上	210	
		1.3					32(12.6)	9(3.5)	3				240	
		1.4					33(13)	9.5(3.7)	2				260	
		1.5					A60-1.5	33(13)	10(3.9)				1.5	
	Hyper Base	1.3L	A60-121314	1.8(26)	20 (7.9)	1	41(16.1)	10(3.9)	2.5	全(Full)	390(13.8)	Minimum or Above 3.7kW(5HP) 或以上	230	
		1.4L	A60-1.5				42(16.5)	10(3.9)					255	
	Hyper Clear	1.3L	A60-121314	2.0(29)	20 (7.9)	1	34(13.3)	8(3.1)	全(Full)	全(Full)	380(13.4)	3.7kW(5HP) 或以上	280	
		1.4L	A60-1.5				35(13.8)	8(3.1)					330	

Tested in Solvent basecoat 1:1
Clearcoat 2:1

Data is tested under the best circumstances